



SELF DRILLING SCREWS JF, JP

สกรูปลายสว่าน JF+, JP+ (รู้ง)

A18

	STANDARD	DIN7981, 7982
	MATERIAL	STEEL
	COATING	YELLOW ZINC
	CODE	ADF, ADP
	UPDATE	23-11-2010

d (Diameter)	#6F	#8F	#10F	#6P	#8P	#10P
p (pitch)	1.3	1.4	1.6	1.3	1.4	1.6
dk	6.8	8.1	9.5	6.9	8.2	9.5
m	4.2	4.7	5.1	4.2	4.6	5

Length (inch)	Size		
	# 6 (3.6mm)	# 8 (4.2mm)	# 10 (4.8mm)
3/8			
1/2	1,000	1,000	1,000
5/8	1,000	1,000	1,000
3/4	1,000	1,000	1,000
1"	1,000	1,000	1,000
1.1/4	1,000	1,000	1,000
1.1/2			
2"		1,000	500
2.1/2		500	500
3"		500	500
3.1/2		500	500
4"		500	500

SELF DRILLING SCREWS, HEXAGON HEAD WITH COLLAR

สกรูหัวเหลี่ยมปลายสว่าน เกลียวห่าง, เกลียวถี่ (รู้ง)

	STANDARD	DIN7504
	MATERIAL	STEEL
	COATING	YELLOW
	CODE	ADX
	UPDATE	23-11-2010

#10	d=4.8	dc=10.5	k=4.45	L1=8	s=8
#12	d=5.5	dc=11	k=5.45	L1=10	s=8
#14	d=6.3	dc=13.2	k=6.45	L1=11	s=10

Size	#10x16G (4.8 mm.)	#10x24G (4.8 mm.)	#12x14G (5.5 mm.)	#12x24G (5.5 mm.)	#14x14G (6.3 mm.)	หัวใหญ่ รู้ง Big Head	#10x16G (4.8 mm.)	#10x24G (4.8 mm.)
5/8 16 mm.	1,000	1,000				5/8 16 mm.	1,000	1,000
3/4 19-20 mm.	1,000	1,000	500	500	500	3/4 19-20 mm.	1,000	1,000
1" 25 mm.	1,000	1,000	500	500	500	1" 25 mm.	1,000	1,000
1.1/4 32-35 mm.	500	500	500	500	250	1.1/4 32-35 mm.	500	500
1.1/2 40 mm.	500	500	250	250	250	1.1/2 40 mm.	500	500
1.3/4 45 mm.			250	250		1.3/4 45 mm.		
2" 50 mm.	500	500	250	250	250	2" 50 mm.	500	500
2.1/4 55 mm.			250	250		2.1/4 55 mm.		
2.1/2 65 mm.	250	250	250	250	250	2.1/2 65 mm.	250	250
3" 75 mm.	250	250	250	250	250	3" 75 mm.	250	250
3.1/2 90 mm.	250	250	250	250	-	3.1/2 90 mm.	250	250
3.3/4 95 mm.	250	250	-	-	-	3.3/4 95 mm.	250	250
4" 100 mm.	250	250	250	250	-	4" 100 mm.	250	250