



HEXAGON SOCKET HEAD CAP SCREWS (AMERICAN STANDARD)

A30

สกรูหัวจมเกลียวอเมริกัน




STANDARD	ANSI B18.3
MATERIAL	12.9
COATING	BLACK
CODE	ASCA
UPDATE	06-11-2008

d (Diameter)	#2	#4	#6	#8	#10
p (pitch)	56	40	32	32	32
k (Head Thickness)			3.5	4	4.8
s (Hex Key)			7/64	9/64	5/32

Length (inch)	Size				
	UNC #2-56	UNC #4-40	UNC #6-32	UNC #8-32	UNF #10-32
1/4					
5/16	1,000		500	500	500
3/8	1,000		500	500	500
1/2	1,000		500	500	500
5/8			500	500	500
3/4			500	500	500
1"			500	500	500
1.1/4			500	500	500
1.1/2			500	500	500
2"			500	500	500

LOW HEAD SOCKET CAP SCREW GRADE 8.8

สกรูหัวจมบาง เกรด 8.8 DIN 7984




STANDARD	DIN7984
MATERIAL	8.8
COATING	BLACK
CODE	ASL
UPDATE	01-03-2008

Size	ราคา	d (Diameter)	M10	M12
10 x 20 mm.		p (pitch)	1.5	1.75
10 x 40 mm.		k (Head Thickness)	6	7
12 x 25 mm.		dk	16	18
12 x 30 mm.		s (Hex Key)	7	8
12 x 40 mm.				

HEXAGON SOCKET SET SCREWS (STANDARD AMERICAN)

ตัวหนอนเกลียวอเมริกัน



STANDARD	ANSI
MATERIAL	12.9
COATING	BLACK
CODE	ASSA
UPDATE	06-11-2008

d (Diameter)	#4	#6	#8	#10
p (pitch)	40	32	32	32
s (Hex Key)		1/16	5/64	3/32

Length (inch)	Size			
	UNC #4-40	UNC #6-32	UNC #8-32	UNF #10-32
3/16				
1/4				
3/8				
1/2				
5/8				
3/4				
1"				