

HEXAGON HEAD BOLTS UNC, UNF (MILD STEEL HEX BOLT-INCH SIZE) A4

สกรูเกลียวหยาบ (NC), เกลียวละเอียด (NF)

	STANDARD	ANSI B18.2.1
	MATERIAL	SWRCH6R (MILD STEEL)
	COATING	BLACK
	CODE	ANC,ANF,BNC,BNF,BFL,BSP
	UPDATE	31-05-2012

d (Diameter)	1/4	5/16	3/8	7/16	1/2	9/16
p (pitch) NC	20	18	16	14	13	12
p (pitch) NF	28	24	24	20	20	18
k (Head Thickness)	4	5.2	6	7.1	7.9	9.1
s (Width across flat)	7/16	1/2	9/16	5/8	3/4	13/16
b	19	22.2	25.4	28.5	31.7	34.9

Length (inch)	Size					
	1/4	5/16	3/8	7/16	1/2	9/16
1/2				บนเส้นคู่=เกลียวตลอด (FULL THREAD)		
3/4						
1"						
1.1/4						
1.1/2						
1.3/4						
2"						
2.1/2						
3"						
3.1/2						
4"						
4.1/2						
5"						
5.1/2	เกลียวครึ่ง(PARTIAL THREAD)					
6"						

บริเวณใต้เส้นคู่ (=) ลงมาเป็นเกลียวครึ่ง

d (Diameter)	1/4	5/16	3/8	7/16	1/2	9/16
p (pitch) NC	20	18	16	14	13	12
p (pitch) NF	28	24	24	20	20	18
M (Thickness)	5.6	6.7	8.3	9.5	11.1	12.3
s (Width across flat)	7/16	1/2	9/16	11/16	3/4	7/8

Size	1/4	5/16	3/8	7/16	1/2	9/16
หัวน็อต NC/NF Hex Nut		500	400	200	100	100
อีแปะดำ Plain Washer		500	400	200	100	100
สปริงดำ Spring Washer		4,000	2,500	1,500	1,000	700