

HEXAGON HEAD BOLTS UNC GRADE 8.8 (HIGH TENSILE / HIGH TENSION BOLT) A6

สลักเกลียวหยาบเหล็กแข็ง (NC) เกรด 8.8

	STANDARD	ANSI B18.2.1
	MATERIAL	8.8
	COATING	BLACK
	CODE	AUC,HUC,BNC-8.8,BFL,BSP
	UPDATE	14-06-2011

d (Diameter)	1/4	5/16	3/8	7/16	1/2	9/16	5/8	3/4	7/8	1"	1.1/8	1.1/4	1.1/2
p (pitch) NC	20	18	16	14	13	12	11	10	9	8	7	7	6
k (Head Thickness)	4	5.2	6	7.1	7.9	9.1	9.9	11.9	13.9	15.5	17.5	19.8	23.8
s (Width across flat)	7/16	1/2	9/16	5/8	3/4	13/16	15/16	1.1/8	1.5/16	1.1/2	1.11/16	1.7/8	2.1/4
b≤6"	19	22.2	25.4	28.5	31.7	34.9	38.1	44.4	50.8	57.1			

Length (inch)	Size													
	1/4	5/16	3/8	7/16	1/2	9/16	5/8	3/4	7/8	1"	1.1/8	1.1/4	1.1/2	
1/2														
3/4														
1"														
1.1/4										บนเส้นคู่=เกลียวตลอด (FULL THREAD)				
1.1/2														
1.3/4														
2"														
2.1/2														
3"														
3.1/2														
4"														
4.1/2														
5"														
5.1/2														
6"														
6.1/2														
7"		ใต้เส้นคู่=เกลียวครึ่ง (PARTIAL THREAD)												
8"														
9"														
10"														

d (Diameter)	3/8	1/2	5/8	3/4	7/8	1"	1.1/8	1.1/4	1.1/2	
p (pitch) NC	16	13	11	10	9	8	7	7	6	
M (Thickness)	8.3	11.1	13.9	16.3	19	21.8	24.6	27	32.5	
s (Width across flat)	9/16	3/4	15/16	1.1/8	1.5/16	1.1/2	1.11/16	1.7/8	2.1/4	

Size	1/4	5/16	3/8	7/16	1/2	9/16	5/8	3/4	7/8	1"	1.1/8	1.1/4	1.1/2
หัวSS400 Nut SS400	500	400	200	100	100	100	100	100	100	50	50	50	50
อึแปะตา Washer	500	400	200	100	100	100	10 kg	10 kg	10 kg	10 kg	10 kg	10 kg	10 kg
สปริงตา Spring	4,000	2,500	1,500	1,000	700	500	350	200	150	100	50	50	30
หัวCL8แท้ Nut Class 8			200		100		100	100	100	50	50	50	50