



HAMMER DRIVE ANCHOR
 พลุ๊กตะปู SANKO (ญี่ปุ่น) B20

 	STANDARD	
	MATERIAL	STEEL
	COATING	CR3
	CODE	PC
	UPDATE	27-10-2008

Size	เส้นผ่านศูนย์กลาง		ความยาว		แรงดึง (kg)		แรงเฉือน (kg)	ความลึก รูดคอนกรีต	กล่องละ Pcs/Box	ลังละ Pcs/Ctn	Unit Price
	เกลียว-ปลัก (d)	สว่าน (D)	ปลัก (L)	เกลียว (H)	ครั้งแรก	ครั้งสุดท้าย					
	C - 645	6	6	6.4	45	15	300	475	652	30	
C - 660	6	6	6.4	60	20	300	475	652	30	50	800
C - 840	8	8	8.5	40	20	450	705	1,030	35	50	800
C - 850	8	8	8.5	50	20	450	705	1,030	35	50	800
C - 870	8	8	8.5	70	25	450	705	1,030	35	50	400
C - 890	8	8	8.5	90	30	450	705	1,030	35	50	400
C - 1050	10	10	10.5	50	20	732	1,180	1,640	40	50	400
C - 1060	10	10	10.5	60	25	732	1,180	1,640	40	50	400
C - 1070	10	10	10.5	70	25	732	1,180	1,640	40	50	300
C - 1080	10	10	10.5	80	25	732	1,180	1,640	40	50	300
C - 1090	10	10	10.5	90	30	732	1,180	1,640	40	50	300
C - 1010	10	10	10.5	100	30	732	1,180	1,640	40	50	300
C - 1012	10	10	10.5	120	30	732	1,180	1,640	40	50	200
C - 1260	12	12	12.7	60	20	1,360	1,826	2,380	50	30	240
C - 1270	12	12	12.7	70	25	1,360	1,826	2,380	50	30	240
C - 1280	12	12	12.7	80	25	1,360	1,826	2,380	50	30	180
C - 1290	12	12	12.7	90	30	1,360	1,826	2,380	50	30	180
C - 1210	12	12	12.7	100	40	1,360	1,826	2,380	50	30	180
C - 1212	12	12	12.7	120	50	1,360	1,826	2,380	50	30	120
C - 1215	12	12	12.7	150	50	1,360	1,826	2,380	50	30	120
C - 1680	16	16	17.0	80	40	2,425	3,215	4,890	60	15	90
C - 1610	16	16	17.0	100	40	2,425	3,215	4,890	60	15	90
C - 1612	16	16	17.0	120	40	2,425	3,215	4,890	60	15	90
C - 1615	16	16	17.0	150	50	2,425	3,215	4,890	60	15	60
C - 1619	16	16	17.0	190	50	2,425	3,215	4,890	60	15	60
C - 2010	20	20	21.5	100	50	3,320	4,450	7,510	80	10	40
C - 2013	20	20	21.5	130	50	3,320	4,450	7,510	80	10	40
C - 2015	20	20	21.5	150	50	3,320	4,450	7,510	80	10	40
C - 2019	20	20	21.5	190	50	3,320	4,450	7,510	80	10	40
C - 2023	20	20	21.5	230	50	3,320	4,450	7,510	80	10	30

